

**RD985**

- Radio Information
- Common
  - Setting
  - Feature Control
  - Microphone/VOX
  - UI Setting
- Conventional
- General Setting
  - Setting
  - Accessories
  - Buttons
  - Telemetry
  - Menu
  - Multi CTC/CDC
  - Network**
  - Access Management
  - CWID
- Zone
- Channel
- Digital Common
- DMR Services
- Scan
- Phone

**Basic Setting**

DHCP

Ethernet IP 192 . 168 . .

Gateway IP 192 . 168 . .

Netmask 252 . 255 . 255 .

Manual Set DNS On/Off

DNS Server IP 8 . 8 . 8 . 8

MAC Address 64 69 BC 04 AE 61

**IP Connect Configuration**

Repeater Type Slave

Jitter Buffer Length 8

Network Authentication Key

Master IP 87 . 106 . 126 . 49

Master UDP Port 50000

IP Connect Networking UDP Port 50000

P2P Firewall Open Timer[sec] 5

IP Multi-site Service

IP Multi-site Service UDP Port 50001

Remote RDAC

Remote RDAC UDP Port 50002

Super Master Service

Super Master IP 192 . 168 . 2 . 205

Close Print Help

**HomeNetwork selbst eintagen**

**leer**

Master Domain Name On/Off

Domain Names

on Programming Interface

Third Party Connect Mode

MOTOTRBO Customer Programming Software - [repeater-dm0zf.ctb]

File Edit View Device Features Remote Window Help

RM Open Save Reports Delete Cut Copy Paste Search Read Write Clone Bluetooth 192.168.11.1

DR 3000

- General Settings
- Accessories
- Security
- Network
- Link Establishment
- Sites
- Talkgroups
- Channels
- Zone1
  - IP-DIG TS1 TS2
  - IP-DIG TS1
  - IP-DIG TS2
  - NO IP-DIG

### Link Establishment

[Top](#) [IP Site Connect](#) [Capacity Plus](#)

Link Type

Authentication Key

Master IP

Master UDP Port

UDP Port

Peer Firewall Open Timer (sec)

Master Archive File

### IP Site Connect

Beacon Duration (ms)

Beacon Interval (sec)

### Capacity Plus

Site ID

Site Alias

Beacon Duration (ms)

Beacon Interval (ms)

Rest Channel/Site IP